

Commercial Air Circulators - 115V

Pedestal & Wall Mount Unit Packs

Oscillating



Adjustable Floor Model

Wall Mount



2 Year Warranty

Features

- 115V, 1/3 HP, 1 Phase, 3 Speed, TEAO Ball Bearing Motor
- A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12' feet of 1/16" diameter cable, 2 cable clamps and instructions.
- Unit Pack ships with Motor, Specified Style Mounting, Propeller & Guard In One Carton
- Pedestal Models Adjust 43" - 63" ; 26" Base Diameter
- Wall Mount Models Include Safety Cable
- 15' Supply Cord and Three Prong Plug Included
- Models are UPS Shippable in One Carton
- Guard Meets OSHA Standards
- Galvanized Steel Propeller
- All Stocked



Type	Tilt (In Degrees) Non-Oscillating	
	Up	Down
Floor	30°	20°
Wall	0°	20°

EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	CFM			RPM			F.L. Amps	Ship Wt.
					High	Med	Low	High	Med	Low		
71567	I-24-OAP	24"	Adjustable Floor	1/3	5548	4699	4062	1100	958	856	3.2	86
71565	I-24-OIW	24"	Wall Mount	1/3								57
71568	I-30-OAP	30"	Adjustable Floor	1/3	7794	5943	5143	1091	871	759	3.2	95
71566	I-30-OIW	30"	Wall Mount	1/3								61

Oscillating Assembled Fan Heads



Features

- Oscillating Fan Heads are not to be used in Upside Down Position
- Motor, Guard, and Propeller are Pre-Assembled
- 30" Head Assembly is UPS OverSize 2

EDP No.	Catalog No.	Prop Dia.	HP	Ship Wt.
71610	24-IAC-MGBO	24"	1/3	46
38422	30-IAC-MGBO	30"	1/3	56

