

Heavy-Duty Air Circulators - 115V

Pedestal, Wall, & I-Beam Mount Fans

Oscillating

Unit Packs, Models - 967 Motor

5 Year Warranty - Ultra Quiet

Features

- 115V, 1/5 HP (18" & 20") and 1/3 HP (24" & 30"), 1 Phase, 3 Speed, Totally Enclosed, Ball Bearing Motor
- Excellent for Churches, Schools, Industrial and Commercial Applications
- Wall and I-Beam Mounts Able To Be Installed By One Individual
- Patented Modular Motor End Dome for Easy Maintenance
- Ultra Quiet Die Cast Aluminum Airfoil Propeller
- 26" Base (18" & 20"); 32" Base (24" & 30")
- Energy Efficient - Lowest Watts Per CFM
- Includes Supply Cord and Plug
- Guards meet OSHA Standards
- 3 Speed Motor



Pedestal



Wall Mount



I-Beam Mount

Motor Tilt Adjustments

Type	Tilt Up or Down (In Degrees)			
	Oscillating		Non-Oscillating	
	Up	Down	Up	Down
Pedestal	20°	10°	20°	10°
Wall	20°	10°	20°	15°
I-Beam	20°	20°	20°	20°
Vertical	N/A	N/A	N/A	N/A

0° = Horizontal Plane

Motor, Specified Mounting, Propeller & Guard Shipped in a Single Carton

EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	CFM			RPM			Motor No.	F.L. Amps	Ship Weight
					High	Med	Low	High	Med	Low			
20894	UP18BN-S	18"	Pedestal	1/5	2600	2113	1805	1125	915	780	967J	1.41	70
20903	UP18WN-S8	18"	Wall Mount	1/5	2600	2113	1805	1125	915	780	967J	1.41	53
20908	UP18IN-S	18"	I-Beam Mount	1/5	2600	2113	1805	1125	915	780	967J	1.41	54
20898	UP20BN-S	20"	Pedestal	1/5	3100	2060	1657	1120	745	600	967J	1.65	71
20904	UP20WN-S8	20"	Wall Mount	1/5	3100	2060	1657	1120	745	600	967J	1.65	53
20909	UP20IN-S	20"	I-Beam Mount	1/5	3100	2060	1657	1120	745	600	967J	1.65	55
20885	UP24BN-S	24"	Pedestal	1/3	5387	4356	3125	1070	850	628	967-3 SP	2.5	87
37129	UP24WN-S8	24"	Wall Mount	1/3	5387	4356	3125	1070	850	628	967-3 SP	2.5	55
37147	UP24IN-S	24"	I-Beam Mount	1/3	5387	4356	3125	1070	850	628	967-3 SP	2.5	59
20890	UP30BN-S	30"	Pedestal	1/3	7996	5859	4063	1045	789	561	967-3 SP	2.9	94
37135	UP30WN-S8	30"	Wall Mount	1/3	7996	5859	4063	1045	789	561	967-3 SP	2.9	61
37148	UP30IN-S	30"	I-Beam Mount	1/3	7996	5859	4063	1045	789	561	967-3 SP	2.9	64

Performance ratings are conducted in accordance with AMCA Standard 230-99.

Notes: Oscillating motor not to be used upside down. See page 10 for optional accessories. A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.

